

# FB 3150 Threaded protectiontube according to DIN 43772 Form 2G, 3G

## Fabricated tube well

<b>Design</b>	2G or 3G to DIN 43772
<b>Process connection</b>	Welded Male threaded
<b>Material</b>	SS 316 - ( Wst 1.4401 )

## Instrument connection

<b>Free moving nut</b>	Male M24x1.5mm standard
<b>Welded nut</b>	Optional: Female nut 1/2

## Stem /Shrank

<b>Insertion length</b>	To specify
<b>DIN43772 Form 2G</b>	Straight over full length
<b>DIN43772 Form 3G</b>	Tip tapered over 50 mm to dia. 9.0 mm
<b>Inside diameter</b>	To suit 6.0mm or 8.0mm sensors

## Process connection

<b>Process connection</b>	1/2
<b>Lagging</b>	To specify
	Other materials: Monel400, Hasteloy C276 or C4, Titanium Gr.II

## Options

Other dimensions  
Tantalum protective jacket

Tube size	Sensor	Form
9 x 1 mm	6.0mm	2G or 3G
11 x 2 mm	6.0mm	2G or 3G
12 x 2.5 mm	6.0mm	2G or 3G
14 x 2.5 mm	8.0mm	2G or 3G
15 x 3 mm	8.0mm	2G or 3G



## Ordering code

\*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model	FB 3150				
Length "U" in mm					
Length "X" in mm					
Form 2G or 3G					
Tube size					

H3-1 Rev. 07/07