

HM5030 AlNiCo Horseshoe magnetic surface thermocouple

Construction

Magnet	Horseshoe AlNiCo magnet
Magnet dimensions	39x26x25mm (LxWxH)
Ingress protection	IP54

Cable

Type	PTFE insulated cable std. Silicon optional
Cable length	4000mm standard

Thermocouple

Calibration	K, T or J
Accuracy	According IEC 584-1
Duplex type	KK, TT or JJ
Hot junction	Free from ground
Insulation test	Minimum 100 Mohm

Temperature limit

Maximum temperature	Measuring tip maximum 240°C
---------------------	-----------------------------

Options

Cable	Other cable type
ATEX	Exi, Exe or Exd
Contact	Sensitive surface contact Spring loaded
Transport protection	Metal frontplate, must be removed to measure
Magnetic strength	90 Newton

Thermokoppel kleurcodes

Thermocouple Extension Type	ANSI	IEC
JX + Iron - Constantan ®		
KX + Chromel ® - Alumel ®		
TX + Copper - Constantan ®		
EX + Chromel ® - Constantan ®		
NX + Nicrosil ® - Nisil ®		
SX + Copper RX - Alloy 11		
BX + Copper-S - Copper-E		


Toleranties volgens IEC 584-2

Type	Class	Temperature range	Fixed value °C	Tolerance to temp. t (°C)
T	1	- 40°C to + 350°C	± 0,5	± 0,004 · t
	2	- 40°C to + 350°C	± 1	± 0,0075 · t
	3	- 200°C to + 40°C	± 1	± 0,015 · t
E	1	- 40°C to + 800°C	± 1,5	± 0,004 · t
	2	- 40°C to + 900°C	± 2,5	± 0,0075 · t
	3	- 200°C to + 40°C	± 2,5	± 0,015 · t
J	1	- 40°C to + 750°C	± 1,5	± 0,004 · t
	2	- 40°C to + 750°C	± 2,5	± 0,0075 · t
	3	-	-	-
K and N	1	- 40°C to + 1000°C	± 1,5	± 0,004 · t
	2	- 40°C to + 1200°C	± 2,5	± 0,0075 · t
	3	- 200°C to + 40°C	± 2,5	± 0,015 · t
R and S	1	0°C to + 1600°C	± 1,0	± [1+0,003 · (t-1100)]°C
	2	0°C to + 1600°C	± 1,5	± 0,0025 · t
	3	-	-	-
B	1	-	-	-
	2	+ 600°C to + 1700°C	± 1,5	± 0,0025 · t
	3	+ 600°C to + 1700°C	± 4	± 0,005 · t



Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.



H1-1 Rev.0 7/07