

TE1830 Standardpanel 3-polig

Application

Female multi panel	Thermocouple and RTD circuits Application: Panel insert for thermocouple and RTD circuits with aluminium frame
Number of circuits	available from 1 thru 6 circuits, to specify
Contacts	Springloaded thermocouple contacts
Materials	Glass filled thermocouple body with original thermocouple material contacts

Temperature rating

Temperature limit	Maximum 200°C
--------------------------	---------------

Construction

Body	Glass filled thermoplastic material
Design	Stainless steel bracket mounted with 2 screws
Molded barriers	Prevent short circuit

Wire size

Accepts wires	From 0.2 mm to 2.0 mm
----------------------	-----------------------

Color code



Thermocouple type	T/C Type Code	ANSI Color Code	IEC Color Code
Iron Constantan	J	Black	Black
Copper Constantan	T	Blue	Brown
Chromel Alumel (NiCr-Ni)	K	Yellow	Green
Nicrosil Nisil	N	Orange	Pink
Chromel Constantan	E	Violet	Violet
Platinum 10% Rhodium	S	Green	Orange
Platinum 13% Rhodium	R	Green	Orange
Uncompensated *	Cu	White	White
Tungsten Rhenium	C	Brown	-

* For Pt.6%Rh. / Pt.30%Rh. B type thermocouple and Pt100 sensors

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model

TE 1830

H9-2 Rev. 0 07/07

Thermo Electra B.V.
Weteringweg 10
2641KM Pijnacker
The Netherlands

Phone +31 (0)15 - 3621200
Fax +31 (0)15 - 3694082
Email sales@thermo.nl
http://www.thermo-electra.com