CA 1004 Fast response thermocouple

Protection tube	
Construction	Closed-end tube
Material	SS316 standard, other materials possible
Insertion length	Customer to specify
Process connection	M20x1.5, 1/2"BSP (G1/2"), 1/2"NPT or other threads possible
Connecton head	
Material	Aluminium, plastic or stainless steel
Cable entry	M20x1.5 cable gland standard, other thread possible
Measuring insert	
Construction	Fixed
Tip	Reduced diameter
Stem diameter	9.0mm standard, other diameters possible
Tip diameter	6.0mm standard, other diameters possible
Thermocouple	
Calibration	K, T, J, E, N, U or L
For duplex	KK, TT, JJ, EE, NN, UU or LL
Accuracy	According IEC 60584
Options	
Transmitter 4-20mA	In-Head transmitter, standard or Ex version. Please select from our standard range or specify your own standard
Swing-Cover head	DAN, transmitter direct mounted on measuring insert
High Swing-Cover head	DAN-H, transmitter in cover, insert with ceramic block

Ordering code

*This datasheet is purely indicative, build-up of model code may vary from this datasheet.

Model	CA 1004		

Calibration

Insertion length "L" in mm

Thermo Electra B.V.
Weteringweg 10
2641KM Pijnacker
The Netherlands

Phone +31 (0)15 - 3621200
Fax +31 (0)15 - 3694082
Email sales@thermo.nl
http://www.thermo-electra.com